



| Modelo  | Producción KG/h | Sup. Calef M <sup>2</sup> | Volumen total M <sup>3</sup> | A mm | B mm | C mm | Peso kg |
|---------|-----------------|---------------------------|------------------------------|------|------|------|---------|
| IFU 20  | 250             | 10,5                      | 1                            | 1600 | 1700 | 1900 | 2000    |
| IFU 40  | 500             | 16                        | 1,5                          | 2400 | 1700 | 1900 | 2400    |
| IFU 60  | 750             | 23                        | 1,6                          | 2300 | 1900 | 2000 | 3000    |
| IFU 80  | 1000            | 31                        | 2,1                          | 2750 | 1900 | 2000 | 3500    |
| IFU 100 | 1250            | 39                        | 3                            | 3100 | 2000 | 2200 | 4500    |
| IFU 125 | 1750            | 48                        | 3,7                          | 3600 | 2000 | 2200 | 5200    |
| IFU 150 | 2000            | 58                        | 4,5                          | 4200 | 2000 | 2200 | 6000    |
| IFU 175 | 2250            | 65                        | 4,8                          | 4000 | 2300 | 2400 | 6750    |
| IFU 200 | 2750            | 75                        | 5,5                          | 4300 | 2300 | 2400 | 7400    |
| IFU 250 | 3250            | 105                       | 6,6                          | 4400 | 2700 | 2700 | 10000   |
| IFU 300 | 4000            | 125                       | 8                            | 5100 | 2700 | 2700 | 12000   |
| IFU 350 | 4500            | 145                       | 9,2                          | 5800 | 2700 | 2700 | 13000   |

INSTMAN FIELD S.A. Se reserva el derecho a cambiar las medidas según el proyecto